



Lasertack

New Laser Generation

MGL-N-556/500~1000mW



LD PUMPED ALL-SOLID-STATE YELLOW LASER AT 556nm

All solid state 556 nm yellow green laser is made features of ultra compact, long lifetime and easy operating, which is widely used in laser medical treatment, scientific experiment, optical instrument, etc.



SPECIFICATIONS

Wavelength (nm)	556±1	
Operating mode	CW	
Output power (mW)	>500, 600, 700, ..., 1000	
Power stability (rms, over 4 hours)	<5%, <10%	
Transverse mode	Near TEM ₀₀	
M ² factor	<3.0	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at the aperture (1/e ² ,mm)	~4.0	
Warm-up time (minutes)	<10	
Polarization ratio	>100:1	
Beam height from base plate (mm)	68.5	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1KHz 1KHz-10KHz, 10KHz-30KHz optional	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-N-556	PSU-H-LED	PSU-H-FDA
<p>245(L)×99(W)×94(H) mm³, 2.6 kg</p>	<p>307 (L) ×150(W) ×106 (H) mm³, 2.9 kg</p>	<p>307 (L) ×150(W) ×106 (H) mm³, 2.9 kg</p>